


Nakrętki sześciokątne samozabezpieczające jednolite
Prevailing torque type (all-metal hexagon nuts), style 2



PN-EN ISO 7042
DIN 980 **PN-M 82176**

Wymiary wg PN-EN ISO 7042 / DIN 980 / PN-M 82176
Dimensions according to PN-EN ISO 7042 / DIN 980 / PN-M 82176

d	M3 ^d	M4 ^d	M5	M6	M8	M10
e min.	6,01	7,66	8,79	11,05	14,38	17,77/18,9 ^d
k max	3,7	4,2	5,1/4,7 ^p	6,0/5,2 ^p	8,0/6,8 ^p	10/8,4 ^p
S	5,5	7	8	10	13	16/17 ^d

d	M12	M14	M16	M18 ^{d,p}	M20	M22 ^{d,p}
e min.	20,03/21,1 ^d	23,36/24,49 ^d	26,75	29,56	32,95	35,03/37,29 ^p
k max	12/10,8 ^p	14,1/14 ^d /12,8 ^p	16,4/16 ^d /14,8 ^p	18/15,8 ^p	20,3/20 ^d /18 ^p	22/19,4 ^p
S	18/19 ^d	21/22 ^d	24	27	30	32


d	M24	M27 ^d	M30 ^{e,d}	M33 ^d	M36 ^{e,d}	M39 ^d
e min.	39,55	45,2	50,85	55,37	60,79	66,44
k max	23,9/24 ^d /21,5 ^p	27	30	33	36	39
S	36	41	46	50	55	60

^d – wg DIN, according to DIN

^p – wg PN-M, according to PN-M

^e – wg PN-EN ISO, according to PN-EN ISO

Nakrętki sześciokątne samozabezpieczające jednolite
Prevailing torque type (all-metal hexagon nuts), style 2



PN-EN ISO 7042
DIN 980 **PN-M 82176**

Klasa wł. mech.: 8, 10
 Property class: 8, 10


- cynkowane / electrolytic zinc

Oferta
Offer

Klasa/ Property class	M4	M5	M6	M8	M10	M12	M14	M16	M18
8	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
10	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Klasa/ Property class	M20	M22	M24	M27	M30	M33	M36
8	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
10	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Nakrętki sześciokątne samozabezpieczające jednolite
Prevailing torque type (all-metal hexagon nuts), style 2



PN-EN ISO 7042
DIN 980 **PN-M 82176**

Stal nierdzewna i kwasoodporna: A2 i A4
 Stainless steel: A2, A4

◇ - nierdzewne A2 / Stainless steel A2
 ◆ - kwasoodporne A4 / Stainless steel A4

Oferta
Offer

M3	M4	M5	M6	M8	M10	M12	M14	M16	M18	M20	M24
◇ ◆	◇ ◆	◇ ◆	◇ ◆	◇ ◆	◇ ◆	◇ ◆	◇ ◆	◇ ◆	◇ ◆	◇ ◆	◇ ◆