


**Nakrętki sześciokątne samozabezpieczające z wkładką niemetalową**  
**Prevailing torque type hexagon nuts (with non-metallic insert)**



**PN-EN ISO 7040**  
**DIN 982**                      **PN-M 82175**

**Wymiary wg PN-EN ISO 7040 / PN-M 82175**  
**Dimensions according to PN-EN ISO 7040 / PN-M 82175**

d	M3 <sup>e</sup>	M4 <sup>e,P</sup>	M5	M6	M8	M10	M12
e min.	6,01	7,66	8,79	11,05	14,38	17,77/18,9 <sup>d</sup>	20,03/21,1 <sup>d</sup>
k max	4,50	6,00/6,3 <sup>P</sup>	6,80/6,7 <sup>P</sup> /6,3 <sup>d</sup>	8,00/7,8 <sup>P</sup>	9,50/10,6 <sup>P</sup>	11,9/12,3 <sup>P</sup> /11,5 <sup>d</sup>	14,9/14,8 <sup>P</sup> /14 <sup>d</sup>
m min	2,15	2,9/4,5 <sup>P</sup>	4,4/4,5 <sup>P</sup>	4,9/5,3 <sup>P</sup>	6,44/8,3 <sup>P</sup>	8,04/9,8 <sup>P</sup>	10,37/12,4 <sup>P</sup>
S	5,50	7	8	10	13	16/17 <sup>d</sup>	18/19 <sup>d</sup>


d	M14	M16	M20	M24	M30 <sup>e,P</sup>	M36 <sup>e,P</sup>
e min.	23,36/24,49 <sup>d</sup>	26,75	32,95	39,55	50,85	60,79
k max	17,0/16,6 <sup>P</sup> /16 <sup>d</sup>	19,1/18 <sup>P,d</sup>	22,8/22,2 <sup>P</sup> /22 <sup>d</sup>	27,1/26 <sup>P</sup> /28 <sup>d</sup>	32,6	38,9
m min	12,1/13,8 <sup>P</sup>	14,1/15,4 <sup>P</sup>	16,9/19 <sup>P</sup>	20,2/20,4 <sup>P</sup>	24,3	29,4
S	21/22 <sup>d</sup>	24	30	36	46	55

<sup>d</sup> – wg DIN, according to DIN

<sup>P</sup> – wg PN-M, according to PN-M

<sup>e</sup> – wg PN-EN ISO, according to PN-EN ISO

**Nakrętki sześciokątne samozabezpieczające z wkładką niemetalową**  
**Prevailing torque type hexagon nuts (with non-metallic insert)**



**PN-EN ISO 7040**  
**DIN 982**                      **PN-M 82175**


Klasa wł. mech.: 8, 10  
 Property class: 8, 10

- cynkowane / electrolytic zinc

Oferta  
 Offer

Klasa/ Property class	M5	M6	M8	M10	M12	M14	M16	M20	M24
8	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
10				<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

**Nakrętki sześciokątne samozabezpieczające z wkładką niemetalową**  
**Prevailing torque type hexagon nuts (with non-metallic insert)**



**PN-EN ISO 7040**  
**DIN 982**                      **PN-M 82175**

Stal nierdzewna i kwasoodporna: A2 i A4  
 Stainless steel: A2, A4

◇ - nierdzewne A2 / Stainless steel A2  
 ◆ - kwasoodporne A4 / Stainless steel A4

Oferta  
 Offer

M5	M6	M8	M10	M12	M16	M20
◇ ◆	◇ ◆	◇ ◆	◇ ◆	◇ ◆	◇ ◆	◇